

MeetingBar A20 Datasheet

All-in-One Android Video Collaboration Bar for Small to Medium Rooms

Yealink MeetingBar A20 is an all-in-one video collaboration bar for small to medium rooms. Featuring a 20MP camera and 120° wide-angle lens, A20 delivers outstanding video quality. Together with the electric lens cap, its AI technologies, including Auto Framing and Speaker Tracking and so on, allow users to experience a smarter and safer [video conference](#). With 8 MEMS microphone arrays and Yealink AI-based noise-proof technology, A20 brings excellent audio experience in small rooms even in full-duplex mode and ensures that everyone can be heard as well as seen. Moreover, A20 combines a computing unit, camera, microphones, speaker, Wi-Fi, and Bluetooth, which provides you with a solution for simple deployment. A20 supports cloud video platforms like [Microsoft Teams](#) and Zoom, so no room PC is required. A20 is capable of content sharing and whiteboard which makes the meeting more communicative and collaborative. Simple and flexible deployment but powerful features deliver excellent video collaboration performance.



Key Features and Benefits

- [All-in-One Design](#)
- [20MP Camera](#)
- [120° Filed of View](#)
- [Electric Privacy Shutter](#)

- Dual Screen
- Auto Framing and Speaker Tracking
- Built-in Bluetooth 4.2
- Built-in Dual-band Wi-Fi
- Content Sharing
- Whiteboard
- Certified by Microsoft Teams & Zoom & BlueJeans & RingCentral

Smart Video Collaboration

Based on Android 10.0 OS, A20 can be operated by just one touch or by the remote control. Also, you can experience a more communicative and collaborative meeting with the content sharing and whiteboard of A20.

See Everyone Clearly

A20 has strong image processing, encoding and decoding capabilities. Besides, with a 20MP camera, it can provide a high-quality video conference experience. With wide 120° field of view, everyone in the conference can be seen without adjusting the camera. Moreover, the image brightness can be automatically optimized even in a dim or backlight environment, ensuring the participant faces can be seen clearly.

Smart Video Conferencing with AI Technology

The A20 camera supports 4K video output, providing you with a face-to-face, intelligent and smooth video experience by accurately reproducing every moment and detail. Featuring multiple AI technologies such as Auto Framing, Speaker Tracking, Picture-in-Picture, and Multi-Focus Framing, users don't need to adjust the camera manually and can focus more on the conference. Precise Sound Localization, Full-Duplex Experience & 8 MEMS microphone arrays make A20 have a strong ability of Yealink AI-based noise proof technology and dereverberation. The Yealink beamforming algorithm, together with the technology of acoustic echo cancellation and dereverberation, brings high-quality full-duplex calls and realizes more precise voice pickup.

Precise Sound Localization, Full-Duplex Experience

8 MEMS microphone arrays make A20 have strong ability of Yealink AI based noise proof technology and dereverberation. The Yealink beamforming algorithm, together with technology of acoustic echo cancellation and the dereverberation, brings high quality full-duplex call and realizes more precise voice pickup.

All-in-One Design for Fast Start


Integrating the computing units, camera, microphones, speaker, Bluetooth, Wi-Fi and bracket, A20 takes up less space and minimizes cable clutter. Plugging in power and HDMI cable gets a video conference ready. In addition, the Yealink Device Management Platform ensures easy management for you.

Wireless Presentation with Low Latency

Cooperating A20 with Yealink wireless presentation pod WPP30, users can start a meeting anywhere in the conference room. WPP30 supports wireless presentation and wireless Device Mode, effectively integrating participants' opinions and improving meeting efficiency. With the Yealink algorithm, WPP30 can maintain a stable wireless connection even in complex network environments and delivers a super clear, speedy and stable presenting experience with low latency.

Specifications

Parameter	Description
Camera	<ul style="list-style-type: none"> • 20 MP Camera • 120° field of view • 8x e-PTZ camera • Electric privacy shutter • 120° DFOV, 110° HFOV, 73° VFOV • Intelligence Features <ul style="list-style-type: none"> - Auto Framing - Speaker Tracking - Picture in Picture - Multi-focus Framing - Smart Gallery (Zoom only)
Audio	<ul style="list-style-type: none"> • Built-in 8 MEMS microphone array with a voice pickup range of 6 meters • Built-in speaker with the maximum volume of 93dB • Yealink Noise Proof Technology • Full-duplex • AGC (Automatic Gain Control) • Echo cancellation • Built-in microphone frequency response: 100Hz to 8kHz • Speaker frequency response: 100Hz to 8kHz
Operating System	<ul style="list-style-type: none"> • Android 10.0
Meeting Features	<ul style="list-style-type: none"> • Calendar • One-click join • Meeting collaboration <ul style="list-style-type: none"> - Content sharing - Whiteboard • Meeting control: <ul style="list-style-type: none"> - Add participates - Hold/Resume - Camera On/Off - Mute/Unmute - Volume Up/Down - Hang up
Video Standard and Network Suitability	<ul style="list-style-type: none"> • Video codecs: H.264 High profile, H.264 SVC, H.264

Network and Security Features	<ul style="list-style-type: none"> • Built-in dual-band Wi-Fi (2.4 GHz/5 GHz) • Built-in Bluetooth 4.2 • IPv4 and IPv6, DHCP/static IP • HTTP/HTTPS web server • TLS 1.2/1.3, AES 256-bit encryption • QoS: 802.1p/q, Diff-serv • VLAN, LLDP • IEEE802.1X <ul style="list-style-type: none"> - EAP-MD5/EAP-TLS - PEAP-MSCHAPv2 - EAP-TTLS/EAP-MSCHAPv2 • Network diagnosis: Ping, Trace route • Time and date synchronization using SNTP • Built-in certificate
Ports	<ul style="list-style-type: none"> • 2 x HDMI output (CEC supported) • HDMI input (through the VCH51 Sharing Kit) • Motion sensor (Teams supported) • 1 x USB 2.0 • 1 x 10 M/100 M/1000 M Ethernet port • 1 x Yealink VCH port (RJ-45) • 1 x Power port • 1 x Security lock slot • 1 x Reset slot
Other Physical Features	<ul style="list-style-type: none"> • Power Adapter: AC 100-240 V Input and DC 48 V/0.7 A Output • USB Output: 5 V  0.5 A • Power consumption (PSU): <ul style="list-style-type: none"> - Standby Power Consumption: 13.9 W - Average Power Consumption: 10.5 W - Peak Power Consumption: 14.2 W • Dimension (W.D.H): 600 mm x 68 mm x 82 mm • Operating humidity: 10 - 90% • Operating temperature: 0 - 40°C • Storage temperature: -30 to + 70°C

<p>Weight</p>	<ul style="list-style-type: none"> • A20-010: <ul style="list-style-type: none"> - N.W/CTN: 2.89 kg - G.W/CTN: 3.48 kg • A20-020: <ul style="list-style-type: none"> - N.W/CTN: 4.93 kg - G.W/CTN: 5.65 kg • A20-025: <ul style="list-style-type: none"> - N.W/CTN: 5.39 kg - G.W/CTN: 6.11 kg
<p>MeetingBar A20 Package</p>	<ul style="list-style-type: none"> • Package contents: <ul style="list-style-type: none"> - MeetingBar A20 endpoint - 3 m Ethernet cable - 2 x 1.8 m HDMI cable - Mounting Bracket and Accessories - TV-Clip Mount - Power adapter - Quick Start Guide - Controller (optional): <ul style="list-style-type: none"> CTP18 Touch Panel VCR20 Remote Control VCR11 Remote Control - Content sharing(optional): <ul style="list-style-type: none"> VCH51 Sharing Kit (HDMI/USB-C) WPP20 Wireless Presentation Pod WPP30 Wireless Presentation Pod • Carton Meas: 674 mm x 136 mm x 195 mm
<p>MeetingBar A20 + CTP18 Package</p>	<ul style="list-style-type: none"> • Carton Meas: 685 mm x 290 mm x 397 mm

MeetingBar Kit

Meeting Room Type	Model	Kit Contain	Related Topic
Small to Medium Meeting Room	A20-010	MeetingBar A20 VCR11	MeetingBar A20
Small to Medium Meeting Room	A20-020	MeetingBar A20 CTP18	MeetingBar A20
Small to Medium Meeting Room	A20-025	MeetingBar A20 WPP30 CTP18	MeetingBar A20
Small to Medium Meeting Room	A20-010-Teams (stop selling)	MeetingBar A20 VCR20	MeetingBar A20

For more information, please go to the [Yealink official website](#).